



1900 Wellworth Ave. • Jackson, MI 49203
517-787-2100

Submittal Data

MODEL
PTHP15G130A-CY

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply		208/230V/60
--------------	--	-------------

Cooling

Capacity	Btu/h	14300/14500
Input	W	1430/1450
Rated current	A	6.4/7.0
EER	Btu/w	10.0/10.0

Heating

Capacity	Btu/h	13200/13600
Rated Input (elect. Heater)	Kw	1210/1245
Rated current	A	19.8/21.9
Max. Current	A	NA

Compressor Electrical

Model		44X362KK&FJMD
Type		ROTARY
Brand		RECHI
Capacitor	mF	30
Refrigerant type	oz	R32/27.5

Air flow & Noise level

Indoor air flow	CFM	412/471
Indoor noise level	dB(A)	48/51
Outdoor noise level	dB(A)	66

Indoor Fan Motor

Model		YDK-25-4
Input	W	70
Capacitor	uF	1.8
Speed(Hi/Lo)	rpm	1150/950

Accessories

Wall Sleeve-breakdown		7602-500F
Stamped Aluminum Grill		7602-501F
Architectural Aluminum Grill		7602-505F
Colored Polymer Grills	See Catalog	
Indoor Discharge Air Deflector		7602-508F
Wireless Wall Thermostat		7602-536A



Outdoor Coil Seacoast Coating

Outdoor Fan Motor

Model		YDK-55-4P2-4
Input	W	104
Speed	RPM	1600

Dimensional Data


Dimension(W*H*D)	inch	41.97x21.1x16.1
Packing (W*H*D)	inch	45.3*24.8*18.9
Net/Gross weight	lbs.	108.03/119.05

System Data

Design pressure		232/493 PSIG
		Remote Controller
Thermostat type		On-Board
		Wired Thermostat

Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-30P



Subbase (no receptical)		7602-509F
Drain Kit		7602-506F
Duct Kit		7602-511F
Universal Remote		7602-512
Thermostat Locking Cover		7602-535